

panoRama Tape

MATERIAL

| | |
|------------------|---|
| Face Film | Optically Clear Polyester |
| Adhesive Inside | Permanent Clear Acrylic - 1 mil (25µ +/-10µ) |
| Adhesive Outside | Semi-Permanent Clear Acrylic - .75 mil (19µ +/-10µ) |
| Liner | Removable Polyester - 1 mil (24µ +/-10µ) |
| Film Thickness | 2 mil (50µ +/-10µ) |
| FR Certification | Not Tested |

DURABILITY

| | |
|----------------------|--|
| Interior | Up to 1 Year |
| Exterior | Not Recommended |
| Environment | Humidity & Solvent Resistance - Good (Indoor Applications Only) |
| Shelf Life | 1 Year |
| Storage Requirements | Store at +59°F to +68°F (+15°C to +20°C) with a Relative Humidity between 45% to 65% |
| Repositionable | Yes |

APPLICATION/REMOVAL

| | |
|------------------|--|
| Application Temp | +50°F to +86°F (+10°C to +30°C) |
| Service Temp | 0°F to +122°F (-17°C to +50°C) |
| Removability | Clean Removal with No Adhesive Residue, up to 6 Months - Adhesion May Increase over Time |
| Removal Temp | +50°F (+10°C) or Greater |
| Exclusions | NOT to Be Applied to Fresh Paint, Polycarbonate, and Some PVC (No Exhaustive List Available) |

Surface must be clean and dry. Prevent contact with solvent or ammonia-based cleaners. For best results, clean glass or install surface with a mild detergent and water and dry thoroughly prior to application. For full installation & removal instructions, please refer to "panoRama Film8020 Application Recommendations."

*For critical substrates and all surfaces, please test PRIOR to application.



Printing Methods

- Not applicable



Material Sizes

- 1" x 200'



Advantages

- Makes Installing Interior Window Graphics Easy - No Professional Installer Needed
- Install Window Graphics Any Time of Year
- Keep Window Graphics Safely on the Inside for Less Vandalism
- Designed for Use with panoRama Film8020 and panoRama Film7030

→ For more information

For additional product information, performance, and warranty guidelines please contact Continental Grafix USA, Inc.

1-704-872-2216 • www.cgxusa.com