



DURATIN BLOCK OUT BANNER 250

(ES420)

Details

- \cdot Unique scratch-resistant coating eliminates the need for lamination.
- Suitable for long-term or high use roll up banners and tradeshow panels.
- · Double layer coating on multilayer PET & PP base with Curl-free lay flat properties
- The satin finish reduces glare, and improves color density.
- · 100% Block out and durable for long-term outdoor use.

Certified for **HP Latex Inks**

Specifications

| Length (ft) | 100 | Width (inch) | 36"/50"/60" |
|-------------------|-------|---------------|-------------|
| Weight (gsm) | 260 | Coating | Resin |
| Caliper (mil) | 10.2 | Base Material | PET & PP |
| Inner Core (inch) | 3 | Printer | ESLU |
| Surface | Satin | | |

KEY FEATURES

- Anti-scratch-resistant coating
- No lamination required
- Eco-sol & HP latex ink compatibility
- 100% block out & Curl-free
- Double side printable with latex & UV

Application

 \cdot High use rollup stands, Trade show panels, Graphics indoor/outdoor POP, Retail aisle banners

General Information

- Printer Profiles are available at HP Media Locator :
 - hp.com/go/mediasolutionslocator
- \cdot Printing Temp : Temperature 15 ~ 30°C (59 ~ 86 °F) / Humidity 30 ~ 60%
- $\cdot \ Lamination: Optional$
- · Storage : Recommended to store in closed original packing in a cool 10 $^{\sim}$ 30 $^{\circ}$ C (50 $^{\sim}$ 77 $^{\circ}$ F) and dry environment. (Humidity 35 $^{\sim}$ 65% RH)
- · Shelf Life: One year, stored in original packing at recommended temperature (Coating warranty guaranteed for 6 months from date of purchase)

How to buy:

- Please call 1-470-359-2111 to place an order or visit www.naturamedia.us for additional information.
- · ICC Profiles are available by calling the above number.

Information provided here is subject to our test criteria and subject to change without prior notice. No media warranty is implied. All material should be tested by purchaser to determine final suitability. Printer and ink change may affect results.