

CLEAR ADHESIVE PVC VINYL MATTE

(SE500)

Details

- · Porous coated (front) and Permanent pressure sensitive self adhesive coated (back)
- · Curl-free, Fast Drying and Good scratch resistant
- · High image definition and excellent durability
- · Cost-effective vinyl with curl free and scratch resistant

Specifications

| Length (ft) | 100 | Width (inch) | 24"/36"/42"/50"/60" |
|-------------------|-------|---------------|---------------------|
| Weight (gsm) | 275 | Coating | Porous |
| Caliper (mil) | 9 | Base Material | PVC |
| Inner Core (inch) | 3 | Printer | PDL |
| Surface | Matte | | |

| Configuration | Thickness (mil) | Structure |
|---------------|-----------------|----------------------|
| Coating | 1.2 | Aqueous Matte |
| Base Material | 3.5 | Vinyl |
| Adhesive | 1.3 | Permanent |
| Release Liner | 3 | Siliconized PET film |
| Total | 9 | tolerance ± 0.2 mil |

KEY FEATURES

- Vinyl with porous coated
- Clear Permanent Self Adhesive
- Water & Scratch Resistant and Curl-free
- Matte Finish for Reduced Glare

Application

· Point of Sales, Point of Purchase Displays, Decals, Bumper Stickers and Posters

General Information

- \cdot Printing Temp : Temperature 15 $^{\sim}$ 30°C (59 $^{\sim}$ 86 °F) / Humidity 30 $^{\sim}$ 60%
- $\cdot \ Lamination: Lamination \ is \ optional.$
- · Storage : Temperature 10 ~ 30°C (50 ~ 77 °F) / Relative Humidity 50%
- · Shelf Life: One year stored in original packaging at recommended conditions.

(Coating warranty guaranteed for 6 months from date of purchase)

How to buy:

- · Please call 1-678-342-1720 to place an order or visit www.naturamedia.us for additional information.
- ICC Profiles are available by calling the above number.

Information provided here is subject to our test criteria and subject to change without prior notice. No media warranty is implied. All material should be tested by purchaser to determine final suitability. Printer and ink change may affect results.