

SOLVENT SEMI-TAC ADHESIVE CLEAR PET FILM

(SO830)

Details

- Optically clear polyester film for window décor
- Semi-tac adhesive leaves no residue upon removal
- Suitable for wide applications with strong adhesion
- Clear adhesive and clear top coating

* Installation Guide

Wet mount recommended

Clean surface before applying. Handle with gloves to avoid marks during printing.

Not recommended for outdoor use. Not suitable for uneven surfaces.

Specifications

Length (ft)	100	Width (inch)	54", 60"
Weight (gsm)	235	Coating	Resin
Caliper (mil)	7.2	Base Material	PET
Inner Core (inch)	3	Printer	ESLUV
Surface	Clear		

KEY FEATURES

- Optically Clear Polyester film
- Semi-tac adhesive
- No residue upon removal
- Wet mount recommended
- Reverse print capable

Application

- Retail window advertisements, indoor window advertisements, retail identification signs, residential interiors, Office privacy, glass partitions and cubicles

General Information

- Printing Temp : Temperature 15 ~ 30°C (59 ~ 86 °F) / Humidity 30 ~ 60%
- Lamination : Optional
- Storage : Recommended to store in closed original packing in a cool 10 ~ 30°C (50 ~ 77 °F) and dry environment. (Humidity 35 ~ 65% RH)
- Shelf Life : One year, stored in original packing at recommended temperature (Coating warranty guaranteed for 6 months from date of purchase)

How to buy :

- Please call 1-470-359-2111 to place an order or visit www.naturamedia.us for additional information.
- **ICC Profiles are available** by calling the above number.

Information provided here is subject to our test criteria and subject to change without prior notice. No media warranty is implied. All material should be tested by purchaser to determine final suitability. Printer and ink change may affect results.