



QM-SGVBF: Everyday gloss bubble free vinyl w/ removable adhesive

A heavy stay flat coated liner and air egress technology allows for easy, bubble-free installation. Solid grey removable adhesive to provide extra blackout for anything under the graphic, allowing your images to “pop”. Use on windows or any smooth mounting surface. This product works well with all “Print & Cut” systems.



Benefits:

- Improved PE Coated Liner
- Bubble Free Application
- Fluorescent True White Point
- Grey Backed for Opacity

Applications:

- Window Display
- Print and Cut Decals
- Rigid Boards
- Bumper Stickers

Registered Latex Developer



TECHNICAL DATA: BUBBLE FREE VINYL W/ REMOVABLE ADHESIVE

SURFACE FINISH:	Gloss	WHITENESS:	143 (CIE Ganz)
BASE MATERIAL:	PVC	OPACITY:	98
ADHESIVE MATERIAL:	Removable Grey Air Egress Acrylic	GLOSS MEASUREMENT:	55 +/- 10% by angle of 60°
LINER MATERIAL:	Double Sided PE Coated Wood Pulp Paper	DURABILITY:	Indoor: Up to 1 year Outdoor: 6 months
LINER WEIGHT:	146 GSM +/- 10%	ROLL LENGTH:	150 Ft.
LINER CALIPER:	7 Mil +/- 1	ROLL WIDTHS:	54"
FACE STOCK WEIGHT:	160 GSM +/- 10%	CORE:	3"
FACE STOCK CALIPER:	4.5 Mil +/- .5	PRINT SIDE:	Print Side Out
BRIGHTNESS:	88 (ISO Blue Whiteness)	INK RECOMENDATIONS:	ES ECO-SOLVENT L LATEX UV UV
STORAGE:	Up to 1 year if stored in proper conditions (cool, dry place 50-80°)		



This media is designed for digital printing applications using OEM printers with their accompanying OEM ink sets. Although designed for all printers using the aforementioned OEM matching ink sets; actual results may vary depending on printer model, age, print design, environmental conditions, and other factors. Exposure of a print to atmospheric pollutants, or to temperature, humidity, and / or lighting extremes can result in fading, color shifting, or other visual changes. The ideal conditions for printing and storage are a temperature of 70°F ±5°F and relative humidity of 50% RH ±3% RH. Our wide format media is guaranteed against manufacturing flaws and defects and is designed to resist printer jams when used properly. Storage: Up to six months if stored in proper conditions (cool, dry place 50-80°)

