





QM-TRITEX7: Lightweight matte hybrid banner

A very unique product. Slightly softer than polypropylene, but has much more strength and durability, virtually tear-proof. Use this unique low cost solution for all of your banner needs. It is a unique alternative to the more expensive Tyvek.



Benefits:

- Extremely Durable
- Wet Strength
- Smooth Non Glare Finish
- Unique & Economical
- Tear Resistant

Applications:

- Hanging Flags
- Posters
- Maps & Architectural Plans
- Tyvek Alternative
- Nautical Maps



| TECHNICAL DATA: LIGHT WEIGHT MATTE HYBRID BANNER | | | |
|--|---------------------------|----------------------|----------------------------------|
| SURFACE FINISH: | Matte | OPACITY: | 95.75 |
| BASE MATERIAL: | Hybrid | DURABILITY: | Indoor: 1 year Outdoor: 6 months |
| BASE WEIGHT: | 140 GSM +/- 3% | ROLL LENGTH: | 200 FT. |
| CALIPER: | 7 Mil +/- 1 | ROLL WIDTHS: | 36" & 60" |
| BRIGHTNESS: | 101 (ISO Blue Whiteness) | CORE: | 3" |
| WHITENESS: | 123 (CIE Ganz) | PRINT SIDE: | Print Side Out |
| GLOSS MEASUREMENT: | 6 +/- 10% by angle of 60° | INK RECOMMENDATIONS: | DRYTONER OFFSET PRESS LATEX WUV |



This media is designed for digital printing applications using OEM printers with their accompanying OEM ink sets. Although designed for all printers using the aforementioned OEM matching ink sets; actual results may vary depending on printer model, age, print design, environmental conditions, and other factors. Exposure of a print to atmospheric pollutants, or to temperature, humidity, and / or lighting extremes can result in fading, color shifting, or other visual changes. The ideal conditions for printing and storage are a temperature of 70°F ±5°F and relative humidity of 50% RH ±3% RH. Our wide format media is guaranteed against manufacturing flaws and defects and is designed to resist printer jams when used properly. Storage: Up to one year if stored in proper conditions (cool, dry place 50-80°)

