



Supreme 300 300STVL

Textured Lightblock Roll-Up Polyester Composite Film

Applications

- Roller banner displays

Benefits

- Unbeatable price-quality ratio - grey back 98% opacity
- Lightly textured surface
- Suitable for indoor and outdoor use
- Scratch resistant, no need for lamination
- Antistatic treatment avoids attracting dust and slipping in the printer
- Stiff, perfect flatness

Post Printing Information for Latex & Solvent Inks:

As with all filmic media, this product must be allowed to “gas-out” after printing.

This can be achieved by leaving the prints face up, ideally 24 hours, to set and harden the unique scratch resistant properties.

If unable to do this e.g. with a long print run, after printing the roll stand it vertically and loosely unwind as much as possible, to allow air in and gases out.

Printability:



Thickness:

310 μ	12.2 mil	415 gsm
-----------------	--------------------	-------------------

Available widths:

914 36"	1067 42"	1270 50"
1372 54"	1524 60"	

Recommended Conditions:

Printroom	15°C - 30°C	30% - 65% RH
Usage	-40°C - 80°C	10% - 90% RH
Storage	10°C - 20°C	20% - 50% RH



KERNOW COATINGS | Kernick Road | Penryn | Cornwall | TR10 9DQ | UK

www.kernowcoatings.com | sales@kernowcoatings.com | T: +44 (0)1326373147

Registered in England | No. 1092182 | A Member of the Sensitisers Group of Companies