

DURATIN SYNTH ROLL UP BANNER


(ES500)

Details

- Unique scratch-resistant coating eliminates the need for lamination
- Great option for long-term or high use rollup banner and tradeshow panels.
- Double layer coating PET & PP base, with anti-curl properties.
- Satin finish reduces glare, and improves color density
- 100% blockout and durable for long-term outdoor use
- Certified for use with HP Latex Inks.

Certified for
HP Latex Inks

Specifications

Length (ft)	100	Width (inch)	36"/50"
Weight (gsm)	165	Coating	Resin
Caliper (mil)	8.7	Base Material	Poly propylene
Inner Core (inch)	3	Printer	
Surface	SATIN		

KEY FEATURES

- High Quality Image Reproduction
- Curl-Free Properties
- Excellent Blockout
- Proprietary Scratch-Resistant Coating
- Durable for Outdoor Use

Application

- Rollup Stands, Trade Show Panels, Indoor/Outdoor POS, Retail Aisle Banners

General Information

- Printing Temp : Temperature 15 ~ 30°C (59 ~ 86 °F) / Humidity 30 ~ 60%
- Lamination : Optional.
- Storage : Recommended to store in closed original packaging in a cool 10 ~ 30°C (50 ~ 77 °F) and dry environment.
(Humidity 35~65% RH)
- Shelf Life : One year stored in original packaging at recommended temperature.
(Coating warranty guaranteed for 6 months from date of purchase)

How to buy :

- Please call 1-470-359-2111 to place an order or visit www.naturamedia.us for additional information.
- [ICC Profiles are available](#) by calling the above number.

Information provided here is subject to our test criteria and subject to change without prior notice. No media warranty is implied. All material should be tested by purchaser to determine final suitability. Printer and ink change may affect results.