



## panoRama White8020

A specialty, self-adhesive, perforated film for unique applications.

Available in an 80/20 film/open ratio.

### APPLICATIONS

- Designer Retail Windows - POP
- Interior Glass Décor - Conference Rooms
- Decorative Trade Show Window Displays

# panoRama White8020

## MATERIAL

Face Film	Printable White Perforated Calendared PVC
Back Side	White
Adhesive	Removable Semi-Permanent Clear Acrylic
Liner	Specialty Liner – 5.3 mil (135µ +/-10µ)
Film Thickness	6 mil (150µ +/-10µ)
Hole Diameter	1.5 mm
FR Certification	Not Tested

## DURABILITY

Interior	Up to 2 years
Exterior	Up to 1 Year - Vertical Exposure under Normal Conditions
Environment	Humidity & Solvent Resistance – Good
Shelf Life	1 Year
Storage Requirements	Store at 59°F to 68°F (+15°C to +20°C) and Relative Humidity between 45% to 65%
Repositionable	No

## APPLICATION/REMOVAL

Application Temp	+50°F to +86°F (+10°C to +30°C)
Service Temp	+0°F to +122°F (-17°C to +50°C)
Removability	Clean Removal with No Adhesive Residue, up to 6 Months – Adhesion May Increase over Time
Exclusions	+50°F (+10°C) or Greater
Application Advice	NOT to Be Applied to Fresh Paint, Polycarbonate, and Some PVC (No Exhaustive List Available)

Surface must be clean and dry. Prevent contact with solvent or ammonia-based cleaners. For best results, clean installation surface with a mild detergent and water and dry thoroughly. ALWAYS clean and dry glass surface prior to application. For full installation and removal recommendations, please refer to "panoRama Exterior Mount Window Film Application & Removal Guide."

*\*For critical substrates and all surfaces, please test PRIOR to application.*



## Printing Methods

- Digital – Solvent, Eco-Solvent, UV, & Latex
- Screen Print



## Material Sizes

- 54" x 100'



## Advantages

- White Front and Back Side Offers Option for Unique Décor Applications
- Calendared Vinyl Provides Great Dimensional Stability
- Special Liner Enables Easy Handling During Printing and Application
- Laminate with panoRama Cast for Maximum Protection and Durability

## → For more information

For additional product information, performance, and warranty guidelines please contact Continental Grapix USA, Inc.

**704-872-2216 • [www.cgxusa.com](http://www.cgxusa.com)**