



## QM-13SBSV: Double-side printable blackout scrim banner

This flexible PVC scrim banner is smooth on both sides and completely opaque. It's bright white color allows for amazing image pop as well as being scratch and water resistant. The fire retardant coating allows it to be used in all environments.



### Benefits:

- 100% Opaque
- Two Side Printable
- Scratch Resistant
- Fire Retardant




### Applications:

- Double Sided Street Banners
- POP Display
- Outdoor Signage

Registered Latex Developer



#### TECHNICAL DATA: DOUBLE-SIDE PRINTABLE BLOCKOUT SCRIM BANNER

SURFACE FINISH:	Matte	GLOSS MEASUREMENT:	6 +/- 10% by angle of 60°
BASE MATERIAL:	PVC	DURABILITY:	Indoor: Up to 1 year Outdoor: Up to 6 months
DENIER:	250D x 250D	ROLL LENGTH:	150 Ft.
BASE WEIGHT:	(13 oz.) 440 GSM +/- 10%	ROLL WIDTHS:	38" & 54"
CALIPER:	13 Mil +/- 1	CORE:	3"
BRIGHTNESS:	85 (ISO Blue Whiteness)	PRINT SIDE:	Print Side Out
WHITENESS :	85 (CIE Ganz)	INK RECOMENDATIONS:	 ECO-SOLVENT  LATEX  UV
OPACITY:	100	STORAGE:	Up to six months if stored in proper conditions (cool, dry place 50-80°)



This media is designed for digital printing applications using OEM printers with their accompanying OEM ink sets. Although designed for all printers using the aforementioned OEM matching ink sets; actual results may vary depending on printer model, age, print design, environmental conditions, and other factors. Exposure of a print to atmospheric pollutants, or to temperature, humidity, and / or lighting extremes can result in fading, color shifting, or other visual changes. The ideal conditions for printing and storage are a temperature of 70°F ±5°F and relative humidity of 50% RH ±3% RH. Our wide format media is guaranteed against manufacturing flaws and defects and is designed to resist printer jams when used properly. Storage: Up to six months if stored in proper conditions (cool, dry place 50-80°)

