



# Reflektion 119 119SGM

## Silver Mirror Polyester Film

### Applications

- Roll-up
- Metallic point of sale displays
- Metallic print proofing

### Benefits

- High gloss coating for maximum mirror finish
- Clear antistatic back-coat avoids attracting dust and slipping in the printer
- Water resistant
- Both sided printable with UV-curable inks

### Post Printing Information for Latex & Solvent Inks:

As with all filmic media, this product must be allowed to “gas-out” after printing. This can be achieved by leaving the prints face up, ideally 24 hours, to set and harden the unique scratch resistant properties. If unable to do this e.g. with a long print run, after printing the roll stand it vertically and loosely unwind as much as possible, to allow air in and gases out.

### Recommended Conditions:

Printroom	59°F - 86°F 15°C - 30°C	30% - 65% RH
Usage	40°F - 176°F -40°C - 80°C	10% - 90% RH
Storage	50°F - 68°F 10°C - 20°C	20% - 50% RH

### Printability:

**(Eco) Solvent** ✓✓✓

**Latex\*** ✓✓✓

**UV** ✓✓✓

### Thickness:

**119** **4.7** **163**  
μ mil gsm

### Available widths:

**1270** **1524**  
50" 60"



www.kernowna.com | info@kernowna.com | (855) 537-6691

\* from 3<sup>rd</sup> Gen HP or later