

# 3516 PolySOL™ Pop-Up Film Satin 12 mil

#### PRODUCT DESCRIPTION

**3516 PolySOL™ Pop-Up Film** is a 12mil polyester display film with a "low glare" satin finish and an instant dry, water resistant coating. The durable 12mil construction is intended to be used unlaminated to create a durable tradeshow panel engineered to withstand repeated rolling in portable display units without cupping, warping or scratching. For additional protection 3516 can be overlaminated with both pressure sensitive and hot laminates



## **ADVANTAGES**

- Stiff Polyester Base / Layflat
- Low Glare Satin Finish
- >99% Opacity / Blockout
- Instant Dry / Water Resistant
- Compatible with PSA & Thermal Overlaminates

## **TECHNOLOGIES**



(soL) Solvent



Latex

#### **APPLICATIONS**

- Durable Tear Resistant Pop-Ups where Blockout is Needed
- Travelling Seminars, Recruitment Sessions, Training Events

## PHYSICAL PROPERTIES

Caliper	12 mil
Basis Weight	420 g/m²
Gloss (60°)	16
Opacity	>99%

<sup>\*</sup>All values listed are target values

### ADDITIONAL INFORMATION

- Available widths: 36"/54" 3" core
- For additional product information please call 1-800-366-7393 or visit our website www.sihlinc.com where you can also find an authorized Sihl reseller near you.