



PERFORMANCE GUIDE

www.Mactac.com

VAL0034

Revised: 06/2016 KSH

6 mil Top-coated Static Cling Vinyl / 60# Liner

Description	Applications and End Uses				
Product	6.0 mil clear gloss top-coated flexible static cling vinyl (no adhesive needed) and a 60 lb liner. This product is ideal for promotional window graphics and automotive oil change decals.				
Face	This product is a self-clinging film, which requires no adhesive, applies quickly to most smooth polished surfaces and is easily removed. Some of the many uses include window advertising, POP window decals, price stickers, automotive window decals and reusable seasonal decals.				
Physical Properties Without Adhesive					
Caliper, in	0.006	ASTM D2103			
Surface Tension	32 dynes				
Temperature Ranges					
Minimum Application Service Ranges	+40°F -10°F to +150°F	CTM #45 Curwood Polyester Film Dry Surface			
Adhesion	Excellent, non-topcoated side of the vinyl will adhere to glass and other highly polished surfaces. It is recommended not to apply the top-coated or printed side to glass as the ink may transfer to the glass upon removal of the film.				
Liner	A 60 Lb. liner for ease of handling and die cutting.				
Caliper, inches	0.0035 +/- 10%	TAPPI T-411			
Durability	Two years (interior of window glass). Up to 6 months from time of application on an outside window. Outdoor climate may limit the bond of static cling on exterior windows. Clear static cling is prone to yellowing with prolonged exposure to UV.				
Shelf Life	Six months when stored at 70° F and 50% relative humidity.				

* Values given are typical for unprocessed product and are not for use as specifications. Processing may change the values.

CALL **1-800-548-3456** for additional product information

IMPORTANT NOTICE: The information given and recommendations made herein are based on our research and are believed to be accurate. In every case, user shall determine before using any product in full scale production, whether such product is suitable for their particular purpose under their own operating conditions. User assumes all risk and liability whatsoever in connection with their use of any product. The products discussed herein are sold without any warranty as to merchantability or any other warranty, expressed or implied. No representative of ours has any authority to waive or change the foregoing provisions unless in a specific agreement signed by the officers of seller and manufacturer. Ultimately, sellers and manufacturers only obligation shall be to replace or credit such quantity of the product proved to be defective at its discretion.

™ Trademark of Morgan Adhesives Company LLC

® Registered Trademark of Morgan Adhesives Company LLC

www.Mactac.com

